




## Current Tire List

Size	Ply	Weight	Tread	Article	Old Article
	<b>RADIAL ALL TRACTION 23° TLR1</b>				
Premium radial for traction, durability and road wear. O.E.M. choice for 2WD, 4WD and MFWD tractors. 23° long bar/long bar tread design sets the standard for the industry.					
24.5R32	1*	589	53	<b>352-926</b>	-
30.5LR32	3*	734	55	<b>356-204</b>	-
900/60R32 (35.5LR32)	176A8	936	61	<b>362-800</b>	-
480/85R34 (18.4R34)	149A8	331	50	<b>362-392</b>	-
520/85R34	162A8	474	52	<b>371-249</b>	352-950
23.1R34	1*	517	52	<b>352-969</b>	-
16.9R38	2*	298	49	<b>352-985</b>	-
480/80R38 (18.4R38)	149A8	365	50	<b>362-341</b>	-
520/85R38 (20.8R38)	155A8	442	52	<b>362-375</b>	-
480/80R42 (18.4R42)	151A8	420	50	<b>362-324</b>	-
480/80R42 (18.4R42)	154A8	428	50	<b>364-092</b>	-
520/85R42 (20.8R42)	157A8	492	52	<b>362-358</b>	-
520/85R42 (20.8R42)	165A8	519	52	<b>369-600</b>	-
14.9R46	4*	318	47	<b>343-323</b>	-
420/80R46	151A8	382	49	<b>352-829</b>	-
420/80R46	4*	406	48	<b>371-640</b>	-
480/80R46	158A8	459	50	<b>362-273</b>	-

	<b>RADIAL 23° TLR1</b>				
Delivers all the benefits of a radial at a great value. 23° long bar/long bar tread design for superior traction and cleaning. O.E.M. choice for combines.					
18.4R34	1*	316	49	<b>354-740</b>	-
15.5R38	1*	242	45	<b>354-767</b>	-
18.4R38	2*	346	49	<b>359-823</b>	-
20.8R38	2*	416	50	<b>362-204</b>	-
18.4R42	3*	380	49	<b>362-212</b>	-
20.8R42	2*	448	50	<b>355-399</b>	-

	<b>RADIAL ALL TRACTION FWD TLR1</b>				
Specifically designed for use on MFWD tractors - O.E.M. choice. Curved bar design for better traction.					
16.9R24	2*	240	49	<b>340-405</b>	-
14.9R26	3*	198	47	<b>340-456</b>	-
420/85R26 (16.9R26)	138A8	250	49	<b>362-528</b>	-
18.4R26	2*	304	50	<b>340-421</b>	-
340/85R28 (13.6R28)	127A8	174	47	<b>362-545</b>	-
380/85R28 (14.9R28)	133A8	221	49	<b>362-562</b>	-
420/85R28 (16.9R28)	139A8	250	48	<b>362-579</b>	-
380/85R30 (14.9R30)	135A8	224	47	<b>362-596</b>	-
420/90R30 (16.9R30)	142A8	272	49	<b>362-613</b>	-

## Current Tire List

Size	Ply	Weight	Tread	Article	Old Article
------	-----	--------	-------	---------	-------------



### **RADIAL ALL TRACTION FWD TLR1**

Specifically designed for use on MFWD tractors - O.E.M. choice. Curved bar design for better traction.

380/85R34 (14.9R34)	137A8	247	47	<b>362-630</b>	-
380/85R34 (14.9R34)	146B	260	47	<b>358-665</b>	-



### **RADIAL DEEP TREAD 23° TLR1W**

23° tread design at a deeper R-1W tread depth. Delivers even wear, long life and smooth ride.

480/80R38 (18.4R38)	149A8	392	63	<b>362-749</b>	-
520/85R38 (20.8R38)	155A8	494	69	<b>362-766</b>	-
650/85R38	173A8	743	70	<b>362-987</b>	-
800/70R38	173A8	970	74	<b>359-548</b>	-
480/80R42 (18.4R42)	151A8	443	63	<b>362-409</b>	-
480/80R42 (18.4R42)	154A8	465	63	<b>364-058</b>	-
520/85R42 (20.8R42)	157A8	528	69	<b>362-426</b>	-
480/80R46 (18.4R46)	158A8	497	63	<b>362-256</b>	-
520/85R46 (20.8R46)	158A8	608	64	<b>362-851</b>	-
480/80R50	159A8	535	63	<b>360-090</b>	-
IF480/80R50	166B	546	63	<b>374-496N</b>	-



### **RADIAL 4000 TLR1W**

Multi-angle R-1W tread designed for Euro-style tractors and wet soil conditions. Used in vineyards and orchards.

7.50R16	102A8	42	33	<b>364-976</b>	-
7.50R18	104A8	42	33	<b>364-993</b>	-
280/70R16	112A8	46	38	<b>365-010</b>	-
280/70R18	114A8	66	38	<b>365-027</b>	-
280/70R20	116A8	67	38	<b>365-826</b>	-
300/70R20	120A8	75	40	<b>365-044</b>	-
360/70R20	129A8	109	40	<b>365-843</b>	-





### **RADIAL 6000 TLR1W**


Multi-angle curved lug design reduces wear on the road while providing good traction in the field. Firm buttressed lugs reduces squirm for long even wear.


280/85R24	115A8	99	49	<b>368-801C</b>	-
320/85R24	122A8	125	50	<b>368-818C</b>	-
340/85R24	125A8	145	55	<b>368-835C</b>	-
380/70R24	125A8	153	54	<b>362-042C</b>	-
420/70R24	130A8	175	55	<b>368-886C</b>	-
340/85R28	127A8	165	60	<b>368-903C</b>	-

## Current Tire List

Size	Ply	Weight	Tread	Article	Old Article
 <p><b><u>RADIAL 7000 TLR1W</u></b> R-1W tread and 45° tread bars for more traction in wet conditions. Wide spaces between lugs ensure thorough self-cleaning and stronger pull.</p>					
460/85R30 (18.4R30)	145A8	277	62	<b>352-683C</b>	-
650/75R30	163A8	537	62	<b>356-220C</b>	-
18.4R34	144A8	303	62	<b>352-691C</b>	-

 <p><b><u>RADIAL 8000 TLR1W</u></b> Designed to be on rear axle of high powered tractors. Gives excellent all round performance in both normal and soft, wet conditions. Longer lugs for improved road wear.</p>					
420/85R30	140A8	251	56	<b>368-920C</b>	-
420/85R34	142A8	275	58	<b>368-937C</b>	-
460/85R34	147A8	313	59	<b>368-971C</b>	-
480/70R34	143A8	295	57	<b>368-954C</b>	-
420/85R38	144A8	299	58	<b>368-988C</b>	-
480/70R38	145A8	326	57	<b>369-005C</b>	-

 <p><b><u>PERFORMER 85 TLR1W</u></b> Designed to be on rear axle of high powered tractors. Gives excellent all round performance in both normal and soft, wet conditions. Longer lugs for improved road wear.</p>					
280/85R24	115B	99	49	<b>377-148N</b>	368-801
320/85R24	131B	107	50	<b>377-165N</b>	368-818
340/85R24	125B	125	55	<b>377-199N</b>	368-835
380/85R24	131B	153	55	<b>376-961N</b>	368-869
420/85R24	137B	191	58	<b>377-182N</b>	368-784
320/85R28	124B	121	52	<b>377-335N</b>	368-852
340/85R28	127B	141	60	<b>377-216N</b>	368-903
380/85R28	133B	163	60	<b>377-301N</b>	370-960
420/85R30	140B	223	56	<b>377-403N</b>	368-920
420/85R34	142B	249	58	<b>377-318N</b>	368-937
460/85R34	147B	291	59	<b>377-233N</b>	368-971
420/85R38	144B	274	58	<b>377-352N</b>	368-988
460/85R38	149B	318	59	<b>377-386N</b>	369-022

 <p><b><u>RADIAL 9000 TLR1W (TRACTOR)</u></b> Multi-angle R-1W tread designed for Euro-style tractors and wet soil conditions. Specially sized for narrow row crop and vegetable farming.</p>					
480/65R24	140A8	235	51	<b>365-673</b>	-
540/65R24	140A8	270	55	<b>359-165</b>	-
540/65R30	150A8	330	54	<b>363-055</b>	-
480/70R34	155A8	361	60	<b>361-763</b>	-
320/85R38 (12.4R38)	138A8	204	51	<b>360-074</b>	-

Size	Ply	Weight	Tread	Article	Old Article
------	-----	--------	-------	---------	-------------



**RADIAL 9000 TLR1W (TRACTOR)**

Multi-angle R-1W tread designed for Euro-style tractors and wet soil conditions. Specially sized for narrow row crop and vegetable farming.

540/65R38	147A8	377	55	<b>359-157</b>	-
600/65R38	153A8	470	59	<b>358-673</b>	-
650/65R38	157A8	541	63	<b>358-185</b>	-
900/50R42	168A8	924	78	<b>359-394</b>	-
380/90R50	151A8	369	57	<b>362-050</b>	-
380/90R54	152A8	403	57	<b>362-069</b>	-



**RADIAL 9000 TLR1W (SPRAYER)**

Multi-angle R-1W tread specifically designed for sprayer applications.

290/95R34	131A8	180	49	<b>359-211</b>	-
320/85R34 (12.4R34)	133A8	182	51	<b>359-238</b>	-
320/85R38 (12.4R38)	143A8	204	51	<b>359-092</b>	-
600/65R38	165A8	505	59	<b>361-933</b>	-
320/90R42 (12.4R42)	139A8	225	52	<b>359-106</b>	-
320/90R46 (12.4R46)	148A8	249	54	<b>357-774</b>	-
380/90R46 (14.9R46)	152B	358	57	<b>359-939</b>	-
230/95R48	134A8	192	49	<b>356-263</b>	-
320/90R50	148A8	262	54	<b>358-118</b>	-



**RADIAL 9000 EVOL TLR1W**

Multi-angle R-1W tread designed for Euro-style tractors and wet soil conditions. Specially sized for narrow row crop and vegetable farming.

540/65R30	150D	303	55	<b>362-834C</b>	-
540/65R34	152D	335	55	<b>371-181C</b>	-
650/65R38	163D	534	63	<b>371-164C</b>	-





**RADIAL 9100 TLR1**

New 105 aspect ratio for large sprayers. Larger footprint for less compaction. Additional lugs for better comfort and wear.

380/105R50	168A8	481	49	<b>362-919</b>	-
------------	-------	-----	----	----------------	---

## Current Tire List

Size	Ply	Weight	Tread	Article	Old Article
					
<b>RADIAL ALL TRACTION DT TLR1W</b>					
Multi-angle R-1W tread for excellent grip and extended tire life. Designed for both broad land and narrow row crop farming.					
320/85R24 (12.4R24)	122A8	137	51	<b>362-681</b>	-
340/85R24 (13.6R24)	125A8	161	53	<b>362-698</b>	-
380/85R24 (14.9R24)	131A8	200	55	<b>362-715</b>	-
480/70R28	140A8	295	55	<b>351-563</b>	-
600/65R28	147A8	388	65	<b>360-058</b>	-
600/70R28	152A8	424	65	<b>365-775</b>	-
380/85R30 (14.9R30)	135A8	241	61	<b>364-551</b>	-
420/90R30 (16.9R30)	145A8	291	62	<b>364-602</b>	-
480/70R30	152A8	335	55	<b>355-569</b>	-
480/80R30 (18.4R30)	145A8	322	62	<b>362-732</b>	-
600/70R30	152A8	428	65	<b>360-163</b>	-
IF600/70R30	159B	432	65	<b>375-703N</b>	-
600/70R30	162A8	441	65	<b>362-307</b>	-
650/75R32	172A8	614	70	<b>361-925</b>	-
800/65R32 (30.5LR32)	172A8	854	74	<b>357-685</b>	-
380/85R34 (14.9R34)	137A8	261	61	<b>364-585</b>	-
420/85R34 (16.9R34)	147A8	308	59	<b>360-155</b>	-
IF420/85R34	152B	340	59	<b>374-513N</b>	-
380/80R38 (14.9R38)	142A8	267	57	<b>360-171</b>	-
600/65R28	154A8	395	65	<b>371-266</b>	-
710/70R38	166A8	759	74	<b>355-542</b>	-
IF710/70R38	178B	739	73	<b>378-219N</b>	-
620/70R42	160A8	620	66	<b>356-271</b>	-
620/70R42	166A8	617	66	<b>374-479N</b>	356-271
710/70R42	168A8	788	74	<b>358-320</b>	-
IF710/70R42	179B	786	74	<b>373-697N</b>	-
320/90R54 (12.4R54)	143A8	277	56	<b>359-580</b>	-
320/90R54 (12.4R54)	149A8	294	56	<b>358-339</b>	-

					
<b>SEVERE SVC RAT DT TLR1W</b>					
Guaranteed against rim slip in land leveling operations.					
710/70R38	171A8	823	74	<b>362-664</b>	-
710/70R42	173A8	815	74	<b>362-115</b>	-

Size	Ply	Weight	Tread	Article	Old Article
------	-----	--------	-------	---------	-------------



**SUPER ALL TRACTION 23° TTR1**

Long-wear premium bias for plowing, fertilizing and planting. O.E.M. choice for 2WD, 4WD, MFWD tractors and combines.

28L-26	14	449	57	351-938	-
18.4-34	8	227	50	343-560	-
20.8-34	8	264	52	343-579	-
16.9-38	8	215	49	343-587	-
18.4-38	8	276	50	343-595	-
20.8-38	10	325	51	343-633	-
20.8-38	8	327	52	343-609	-
18.4-42	10	303	50	343-641	-
20.8-42	10	358	52	343-668	-



**SUPER ALL TRACTION 23° TLR1**

Long-wear premium bias for plowing, fertilizing and planting. O.E.M. choice for 2WD, 4WD, MFWD tractors, combines, and construction equipment.

23.1-26	8	329	53	344-095	-
23.1-26	12	356	53	344-052	-
23.1-26	14	383	53	362-460	-
28L-26	12	423	57	344-060	-
24.5-32	12	389	53	344-079	-
30.5L-32	12	576	54	344-087	-
30.5L-32	14	613	54	351-067	-
30.5L-32	16	630	54	351-075	-
18.4-34	12	264	50	343-676	-
23.1-34	8	387	53	344-109	-
12.4-38	14	210	45	355-577	-
18.4-38	14	337	50	343-692	-
20.8-42	14	406	52	352-888	-



**SUPER ALL TRACTION 23° HD TLR1 SS**

Designed for cotton picker applications. Rounded shoulder to eliminate tread lug compression. Stronger carcass.

520/85D38 (20.8D38)	173A8	481	46	363-038	-
---------------------	-------	-----	----	---------	---



**SUPER ALL TRACTION FWD TLR1**

Specifically designed for front positions of MFWD tractors and a perfect mate for our SAT 23°. Excellent wear resistance.

16.9-24	10	200	49	343-889	-
14.9-26	10	174	48	343-897	-
16.9-26	10	220	49	343-900	-
18.4-26	6	228	50	343-846	-

## Current Tire List

Size	Ply	Weight	Tread	Article	Old Article
------	-----	--------	-------	---------	-------------



### **SUPER ALL TRACTION FWD TLR1**

Specifically designed for front positions of MFWD tractors and a perfect mate for our SAT 23°. Excellent wear resistance.

18.4-26	10	251	50	<b>343-919</b>	-
13.6-28	10	161	47	<b>343-927</b>	-
14.9-28	10	189	48	<b>343-935</b>	-
16.9-28	10	231	49	<b>343-943</b>	-
14.9-30	10	198	47	<b>343-951</b>	-



### **SUPER ALL TRACTION II 23° TLR1**

Modern tread design to maximize traction and improve ride. Increased footprint minimizes soil compaction. Increased number of lugs vs. Traction Field & Road for better road wear and ride.

200/85D14	92A6	27	32	<b>365-571</b>	-
250/85D16.5	8	48	40	<b>365-401</b>	-
9.5-24	6	65	40	<b>371-351</b>	338-370
11.2-24	4	83	41	<b>365-163</b>	357-995
11.2-24	8	87	41	<b>365-180</b>	352-012
12.4-24	4	98	43	<b>365-299</b>	-
12.4-24	8	101	43	<b>365-231</b>	-
13.6-24	8	125	43	<b>369-719</b>	345-318
14.9-24	6	128	44	<b>365-061</b>	-
14.9-24	8	130	48	<b>373-238</b>	358-002
12.4-28	6	110	43	<b>365-452</b>	-
13.6-28	6	124	44	<b>365-265</b>	-
14.9-28	6	147	44	<b>365-078</b>	351-830
16.9-28	6	170	47	<b>365-469</b>	351-679
16.9-30	6	174	47	<b>365-282</b>	-
18.4-30	8	222	49	<b>365-486</b>	-
18.4-34	8	242	49	<b>367-203</b>	338-567
15.5-38	8	184	44	<b>367-186</b>	338-095
18.4-38	8	255	50	<b>367-220</b>	-
20.8-38	8	340	52	<b>367-237</b>	-



### **TRACTION FIELD & ROAD TTR1**

A great general agricultural tire with 23° tread and a value price. Full range of sizes available. Also used on construction compaction equipment.

12.4-16	4	66	45	<b>345-202</b>	-
14.9-26	6	121	48	<b>345-288</b>	-
16.9-26	6	155	48	<b>355-119</b>	-
18.4-26	8	197	50	<b>345-326</b>	-
18.4-28	6	185	50	<b>338-494</b>	-
23.1-30	8	342	53	<b>338-613</b>	-
23.1-30	12	344	53	<b>364-857</b>	-

Size	Ply	Weight	Tread	Article	Old Article
------	-----	--------	-------	---------	-------------



**TRACTION FIELD & ROAD TTR1**

A great general agricultural tire with 23° tread and a value price. Full range of sizes available. Also used on construction compaction equipment.

16.9-34	6	173	49	338-060	-
9.5-36	4	73	40	338-443	-
13.6-38	4	144	47	338-036	-
13.6-38	6	157	47	338-087	-
14.9-38	6	180	48	338-516	-
16.9-38	6	194	49	338-141	-
9.5-42	6	90	45	338-532	-



**SUPER ALL TRACTION II 23° TLR1**

A great general agricultural tire with 23° tread and a value price. Full range of sizes available. Also used on construction compaction equipment.

9.5-16	4	46	40	376-808N	351-814
--------	---	----	----	----------	---------



**TRACTION FIELD & ROAD TLR1**

A great general agricultural tire with 23° tread and a value price. Full range of sizes available. Also used on construction compaction equipment.

18.4-16.1	8	155	50	359-564	-
8.3-24	4	47	38	351-644	-
12.4-24	12	112	45	357-987	-
16.9-24	8	155	49	359-505	-
18.4-26	12	223	50	362-443	-
13.6-28	12	138	47	361-917	-
12.4-42	6	140	45	355-097	-
12.4-42	10	165	45	358-630	-







**FIELD & ROAD TTR1**

Great value in a replacement rear for older tractors. 23° long bar/long bar tread.

11.2-28	4	72	37	304-743	-
11.2-28	6	78	37	361-623	-
9.5-32	4	61	36	304-794	-
11.2-36	4	90	37	304-808	-
12.4-36	4	102	39	304-816	-
12.4-36	10	135	39	319-872	-
13.6-36	4	115	41	304-824	-
11.2-38	4	96	37	304-832	-
12.4-38	4	111	39	304-840	-
12.4-38	6	122	39	304-921	-
12.4-38	8	127	39	354-805	-

## Current Tire List

	Size	Ply	Weight	Tread	Article	Old Article
	<b><u>FIELD &amp; ROAD TLR1</u></b>					
	Great value in a replacement rear for older tractors. 23° long bar/long bar tread.					
	11.2-38	4	99	37	355-003	-
	<b><u>PULLER 2000 TLP1</u></b>					
	The only tire designed specifically for pulling competitions. Full-width tread for more ground contact and special puller rubber compound for maximum pull.					
	24.5-32	10	396	8	369-685	358-096
	30.5L-32	HP	471	8	361-992	-
	<b><u>IRRIGATION SPECIAL TTR1</u></b>					
	Extra-deep 23° tread with large footprint for less compaction and better traction in mud. Rugged nylon cord body with flexible sidewall and tough tread rubber.					
	11.2-24	4	64	32	349-984	-
	14.9-24	4	107	36	322-679	-
	<b><u>IRRIGATION SPECIAL TLR1</u></b>					
	Extra-deep 23° tread with large footprint for less compaction and better traction in mud. Rugged nylon cord body with flexible sidewall and tough tread rubber.					
	380/85D24	C	118	35	373-765N	-
	11.2-24	4	65	32	321-893	-
	14.9-24	4	108	36	322-377	-
	<b><u>RADIAL CHAMP SPADE GRIP TLR2</u></b>					
	Longer footprint for more traction in muddy soil conditions. Excellent for rice and sugar cane applications.					
	16.9R28	2*	307	94	352-527	-
	18.4R28	2*	384	100	352-748	-
	16.9R30	3*	313	94	359-386	-
	18.4R38	2*	449	100	353-140	-
	20.8R38	2*	559	105	353-167	-
	18.4R42	2*	505	100	354-376	-
	480/70R34	146A8	385	100	369-668N	-
	520/85R34	162A8	525	105	371-232N	-
	520/85R42 (20.8R42)	157A8	616	105	371-198	-
	520/85R42 (20.8R42)	165A8	671	105	371-215N	371-198
	320/90R46 (12.4R46)	148A8	268	82	363-004	-
	18.4R46	3*	538	100	359-378	-
520/85R46 (20.8R46)	158A8	637	105	369-651N	-	

Size	Ply	Weight	Tread	Article	Old Article
------	-----	--------	-------	---------	-------------



**CHAMPION SPADE GRIP TTR2**

Extra-deep 23° tread with large footprint for less compaction and better traction in mud. O.E.M. choice for rice and sugar cane applications.

14.9-24	8	200	90	352-837	-
23.1-30	8	434	109	311-189	-
24.5-32	10	546	112	311-626	-
18.4-34	6	305	100	311-154	-
23.1-34	8	513	109	311-375	-
13.6-38	6	191	86	332-984	-
15.5-38	6	239	86	311-219N	-
18.4-38	8	364	100	311-448	-
20.8-38	10	472	105	311-529	-
13.6-46	6	236	86	332-976	-



**CHAMPION SPADE GRIP TLR2**

Extra-deep 23° tread with large footprint for less compaction and better traction in mud. O.E.M. choice for rice and sugar cane applications.

14.9-24	12	219	90	359-610	-
16.9-26	10	242	94	326-712	-
18.4-26	6	279	100	358-266	-
18.4-26	10	277	100	326-445	-
23.1-26	10	424	100	362-647	-
28L-26	12	584	109	358-282	-
18.4-30	6	280	100	358-274	-
18.4-30	10	301	100	342-432	-
30.5L-32	14	762	114	358-231	-
35.5L-32	12	932	120	358-258	-
18.4-38	14	411	100	343-110	-
20.8-38	14	516	105	351-970	-
20.8-42	14	600	103	352-918	-



**ALL NON-SKID TRACTOR TTR3**

Button tread for minimum soil disturbance. O.E.M. choice for combines, grain wagons and highway mowers.

9.5-24	4	41	14	306-096	-
13.6-28	6	105	24	306-193	-

Size	Ply	Weight	Tread	Article	Old Article
------	-----	--------	-------	---------	-------------



**ALL NON-SKID TRACTOR TLR3**

Button tread for minimum soil disturbance. O.E.M. choice for combines, grain wagons, highway mowers and compaction equipment.

18.4-16.1	6	123	28	320-943	-
8.3-24	4	48	18	351-733	-
14.9-24	6	126	23	359-556	-
16.9-24	6	154	28	351-709	-
16.9-24	10	175	28	358-789	-
18.4-26	6	193	29	315-958	-
18.4-26	12	211	29	369-753	315-966
23.1-26	8	262	21	345-377	-
23.1-26	12	287	21	323-527	-
28L-26	12	312	21	351-008	-
28L-26	16	392	21	362-220	-
24.5-32	12	391	35	322-296	-
24.5-32	16	499	35	360-384	-
30.5L-32	14	533	38	359-904	-
30.5L-32	16	627	38	357-758	-
35.5L-32	20	709	39	357-820	-



**ALL NON-SKID II TRACTOR TLR3**

Button tread for minimum soil disturbance. O.E.M. choice for combines, grain wagons and highway mowers.

28L-26	12	381	34	351-857	-
28L-26	16	437	34	362-085	-



**TURF & FIELD TTR3**

Excellent for drive axle use in golf courses and parks. Treads lightly on the green; no special rims are required.

13.6-16 (7R)	4	61	12	345-210	-
--------------	---	----	----	---------	---




**TURF & FIELD TLR3**


Excellent for drive axle use in golf courses and parks. Treads lightly on the green; no special rims are required.


9.5-16	6	42	19	351-776	-
21.5L-16.1	6	186	33	312-770	-
21.5L-16.1	10	193	33	355-887	-
9.5-22	4	49	19	358-649	-


## Current Tire List


Size	Ply	Weight	Tread	Article	Old Article
					
<b><u>FLOTATION ALL TERRAIN TLHF1</u></b>					
Weight distributed across huge footprint for less compaction. Great at low inflation pressures for flotation over soil and sand.					
66X44.00-25	6	508	13	341-940	-
66X44.00-25	16	689	13	354-511	-
57X31.00-26	6	349	13	362-077	-
					
<b><u>FLOTATION ALL TERRAIN WTP TLHF1</u></b>					
Weight distributed across huge footprint for less compaction. Great at low inflation pressures for flotation over soil and sand.					
66X44.00-25	16	738	13	361-747	-
66X44.00-25	20	736	13	371-674	-
					
<b><u>FLOTATION FREE ROLLING TLHF2</u></b>					
Gives fertilizer trucks long wear on paved roads and traction in wet fields. Delivers moderate steering traction.					
48X25.00-20	12	298	32	360-422	-
48X31.00-20	14	361	32	360-430	-
					
<b><u>FLOTATION 23° ( CENTER RIB) TLHF2</u></b>					
Center rib for extended driving on pavement during transportation. 23° high-flotation tread design.					
48X25.00-20	10	260	32	328-057	-
					
<b><u>FLOTATION 23° (CENTER RIB) TLHF2</u></b>					
Center rib for extended driving on pavement during transportation. 23° high-flotation tread design.					
48X31.00-20	14	317	32	361-984	-
					
<b><u>FLOTATION 23° DEEP TREAD TLHF3</u></b>					
Large footprint, deep 23° tread for flotation, traction and long wear. Firestone's top-of-the-line for high horsepower tractors.					
42X25.00-20	12	279	58	358-304	-
48X25.00-20	10	355	58	344-184	-
48X31.00-20	14	422	58	361-976	-
54X37.00-25	12	588	61	352-055	-
66X43.00-25	10	830	74	340-693	-
66X43.00-25	16	862	74	358-312	-
73X44.00-32	12	1048	77	328-669	-


Size	Ply	Weight	Tread	Article	Old Article
 <p><b>FLOTATION 23° DEEP TREAD TLHF3</b> Large footprint, deep 23° tread for flotation, traction and long wear. Firestone's top-of-the-line for high horsepower tractors.</p>					
73X44.00-32	16	1116	77	358-835	-
76x50.00-32	16	1591	80	359-866	-
76x50.00-32	20	1620	80	369-702	-


 <p><b>RADIAL FLOTATION 23° TLHF3</b> All the advantages of a radial in a flotation tire. Large footprint minimizes yield-robbing compaction.</p>					
1050/50R25	172B	1065	74	359-041	-


 <p><b>FLOTATION IMPLEMENT TLI3</b> Designed for free rolling wheels on trailers, wagons and implements. Carries heavy loads while minimizing damage to fields and crops.</p>					
600/55-22.5	16	320	35	364-653	-
700/50-22.5	16	342	35	359-033	-


 <p><b>CHAMPION GUIDE GRIP SINGLE RIB TTF1</b> Perfect for wet cane and rice fields. Smooth tread with one heavy rib.</p>					
5.50-16	4	18	30	342-920	-


 <p><b>CHAMPION GUIDE GRIP SINGLE RIB TLF1</b> Perfect for wet cane and rice fields. Smooth tread with one heavy rib.</p>					
10.00-16	6	52	37	340-588	-


 <p><b>CHAMPION GUIDE GRIP 4-RIB TTF2</b> 4-rib tread gives flotation and resistance to side slip. O.E.M. preferred tire.</p>					
11L-15	8	45	27	339-806	-
6.00-16	6	22	20	368-019	-
10.00-16	8	45	27	339-814	-


Size	Ply	Weight	Tread	Article	Old Article
 <p><b>CHAMPION GUIDE GRIP 4-RIB TLF2</b> 4-rib tread gives flotation and resistance to side slip. O.E.M. preferred tire.</p>					
9.5L-15	8	36	23	<b>375-227</b>	368-478
11L-15	8	49	34	<b>376-570N</b>	-
7.50-16	8	32	20	<b>374-717</b>	367-985
6.50-16	6	28	19	<b>368-036</b>	339-741
7.50-16	6	36	20	<b>368-002</b>	-
10.00-16	6	49	27	<b>339-849</b>	-
10.00-16	8	52	27	<b>339-865N</b>	-
10.00-16	10	53	27	<b>368-750</b>	-
11.00-16	8	67	29	<b>339-873</b>	-
11.00-16	12	77	29	<b>342-602</b>	-
14L-16.1	8	89	33	<b>365-537</b>	-
14L-16.1	12	101	33	<b>359-432</b>	-
16.5L-16.1	8	131	36	<b>339-938</b>	-


 <p><b>GUIDE GRIP 3-RIB TTF2</b> Wide 3-rib design for all types of farming conditions. Rugged Firestone construction.</p>					
5.00-15	4	12	12	<b>375-278N</b>	368-274


 <p><b>GUIDE GRIP 3-RIB TLF2</b> Wide 3-rib design for all types of farming conditions. Rugged Firestone construction.</p>					
7.5L-15	6	27	19	<b>374-666N</b>	368-291


 <p><b>CHAMPION GUIDE GRIP 3-RIB TTF2</b> Wide 3-rib design for all types of farming conditions. Rugged Firestone construction.</p>					
6.50-16	6	26	22	<b>374-683</b>	368-393
10.00-16	8	52	33	<b>350-877</b>	-
11.00-16	8	70	35	<b>350-885</b>	-
7.50-20	6	46	26	<b>352-594</b>	-


Size	Ply	Weight	Tread	Article	Old Article
 <p><b><u>CHAMPION GUIDE GRIP 3-RIB TLF2</u></b> Wide 3-rib design for all types of farming conditions. Rugged Firestone construction.</p>					
11L-15	8	45	27	375-142	339-806
6.00-16	6	24	19	374-700	368-376
7.50-16	8	39	24	374-751	368-427


 <p><b><u>CHAMPION GUIDE GRIP 3-RIB HD TLF2</u></b> 3-rib design with heavier-duty construction. Self-cleaning tread.</p>					
14L-16.1	8	81	41	354-449	-
14L-16.1	10	96	41	322-687	-
11.00-24	12	121	35	359-440	-


 <p><b><u>3-RIB STUBBLE STOMPER TLF2</u></b> Wide 3-rib design for all types of farming conditions. High-density rubber to resist stubble-related wear and damage.</p>					
10.00-16	8	61	33	357-847	-
11.00-16	8	80	35	357-855	-


 <p><b><u>4-RIB STUBBLE STOMPER TLF2</u></b> 4-rib tread gives flotation and resistance to side slip. High-density rubber to resist stubble related wear and damage.</p>					
10.00-16	8	56	27	357-898	-
11.00-16	8	76	27	357-901	-

 <p><b><u>IMPLEMENT STUBBLE STOMPER TLI1</u></b> High-density rubber makes no-till no problem. Special cut-resistant sidewall.</p>					
5.90-15	4	19	7	362-034	-
31X13.50-15	10	69	12	359-025	-

 <p><b><u>TURF STUBBLE STOMPER TLG2</u></b> Perfect for golf course and park work. Rugged stubble stomper tread rubber for long, reliable wear.</p>					
31X13.50-15	10	62	11	362-190	-

Size	Ply	Weight	Tread	Article	Old Article
 <h3><b>HIGHWAY SPECIAL TL1</b></h3> <p>D.O.T. approved for highway speeds with intermittent highway use only. Several sizes available.</p>					
9.5L-15FI	E	45	11	<b>374-598</b>	364-738
11L-15FI	F	56	11	<b>374-581</b>	364-772
12.5L-15FI	F	67	11	<b>374-564</b>	364-806

 <h3><b>FARM IMPLEMENT TT1</b></h3> <p>Designed for free-rolling wheels on wagons and trailers. Stubble stomper high-density tread rubber and cut-resistant sidewall.</p>					
8.5L-14	6	20	8	<b>339-148</b>	-
6.70-15	6	17	7	<b>339-164</b>	-
6.00-16	6	17	8	<b>339-199</b>	-
12.5L-16	8	40	8	<b>339-474</b>	-

 <h3><b>FARM IMPLEMENT TL1</b></h3> <p>Designed for free-rolling wheels on wagons and trailers. Stubble stomper high-density tread rubber and cut-resistant sidewall.</p>					
9.5L-14	8	28	8	<b>358-940</b>	-
11L-14	8	32	8	<b>350-028</b>	-
5.90-15	4	15	7	<b>339-288</b>	-
6.70-15	4	18	7	<b>339-296</b>	-
6.70-15	6	18	7	<b>375-652N</b>	-
7.60-15	8	24	8	<b>339-369</b>	339-229
9.5L-15	8	30	8	<b>339-377</b>	339-237
9.5L-15	12	36	8	<b>355-860</b>	-
11L-15	8	33	8	<b>339-547</b>	339-431
11L-15	12	41	8	<b>339-482</b>	-
12.5L-15	10	40	8	<b>339-598</b>	-
12.5L-15	12	47	8	<b>354-538</b>	-
12.5L-15	18	48	7	<b>378-457N</b>	-
27X9.50-15	8	28	10	<b>357-804</b>	351-792
11L-16	8	37	8	<b>359-831</b>	339-466
12.5L-16	12	50	8	<b>339-490</b>	-
12.5L-16	14	61	8	<b>356-840</b>	-
14L-16.1	8	70	12	<b>354-686</b>	-
14L-16.1	12	83	12	<b>365-520</b>	-
16.5L-16.1	8	87	14	<b>339-628</b>	-
16.5L-16.1	10	109	14	<b>339-636</b>	-
16.5L-16.1	14	120	14	<b>342-483</b>	-
7.50-20	6	35	8	<b>339-326</b>	-

Size	Ply	Weight	Tread	Article	Old Article
------	-----	--------	-------	---------	-------------



**FARM TIRE TL11**

Designed for free rolling wheels of wagons and trailers. Tread design is similar to passenger car tires.

10.00-15	8	43	11	329-614	-
----------	---	----	----	---------	---



**FARM TIRE L TL11**

Designed for free rolling wheels on wagons and trailers. Shock-fortified nylon cord body.

19L-16.1	12	119	16	359-777	-
21.5L-16.1	10	148	14	318-507	-
21.5L-16.1	14	164	14	325-848	-



**RIB PLANTER SINGLE RIB TT11**

Single rib aids in planting. Tough Firestone construction.

4.00-18	4	12	25	368-529	350-893
---------	---	----	----	---------	---------



**RIB IMPLEMENT TT11**

5 rib tread enables tire to grip hillsides. A versatile tire for many kinds of free-rolling applications.

5.00-15	4	12	6	375-346N	368-512
4.00-18	4	10	7	368-087	-
9.00-24	8	54	12	356-212	-



**RIB IMPLEMENT TL11**

5 rib tread enables tire to grip hillsides. A versatile tire for many kinds of free-rolling applications.

31X13.50-15	8	55	12	355-518	-
31X13.50-15	12	66	12	358-622	-
11.25-20	14	73	13	362-970N	-
11.25-24	8	77	13	324-221	-
11.25-24	12	96	13	355-534	-
11.25-28	12	116	13	326-453	-

	Size	Ply	Weight	Tread	Article	Old Article
	<p><b><u>DUO RIB PLANTER TTI1</u></b>                      Specifically designed for firming soil around seed as it's planted. Extra-deep ribs keep tractor in line.</p>					
	7.60-15	6	24	21	325-864	-
	<p><b><u>DUO RIB PLANTER TLI1</u></b>                      Specifically designed for firming soil around seed as it's planted. Extra deep ribs keep tractor in line.</p>					
	7.50-20	4	45	24	313-424	-
	<p><b><u>RIB DUPLEX FARM TLI1</u></b>                      Wide rib tread for excellent flotation. Non-directional tread design.</p>					
	36X16-17.5	8	111	16	318-523	-
	36X16-17.5	14	123	16	361-968	-
	<p><b><u>ALL NON-SKID FARM TLI2</u></b>                      Implement application for minimum ground disturbance. Non-aggressive multi-block tread.</p>					
	16.5L-16.1	6	83	19	310-514	-
	13.50-16.1	10	90	19	325-015	-
	16.5L-16.1	10	100	19	317-365	-
	<p><b><u>POWER IMPLEMENT (a) TLI3</u></b>                      Designed for traction wheels on self-powered machines like loaders. Delivers performance and long wear.</p>					
	5.00-15	4	15	15	310-069	-
	<p><b><u>POWER IMPLEMENT (b) TLI3</u></b>                      Designed for traction wheels on self-powered machines like loaders. Delivers performance and long wear.</p>					
	7.60-15	6	26	16	340-529	340-510
	21.5L-16.1	8	190	33	359-408	-
	21.5L-16.1	14	219	33	359-416	-

Size	Ply	Weight	Tread	Article	Old Article
------	-----	--------	-------	---------	-------------



**POWER IMPLEMENT (c) TLI3**

Designed for traction wheels on self-powered machines like loaders. Delivers performance and long wear.

13.50-16.1	8	85	23	342-688	-
------------	---	----	----	---------	---



**NON-DIRECTIONAL DUPLEX FARM TLI3**

Wide tread reduces compaction. Non-directional tread designed to provide positive traction.

40X19-19.5	14	197	26	323-004	-
------------	----	-----	----	---------	---



**FOR SPL WTP CRC TTLS2**

Built specifically for logging service with CRC (Cut Resistant Compound). 23° tread bar is 25% deeper at center; up to 42% thicker than agricultural tires.

18.4-26	10	334	64	361-771	-
23.1-26	10	516	67	361-798	-
23.1-26	14	547	67	361-801	-
16.9-30	10	350	61	361-844	-
18.4-34	10	390	64	361-887	-
28L-26	12	680	70	362-477	361-828
28L-26	14	698	70	362-494	361-836



**FOR SPL WTP CRC TLLS2**

Built specifically for logging service with CRC (Cut Resistant Compound). 23° tread bar is 25% deeper at center; up to 42% thicker than agricultural tires.

24.5-32	16	746	70	364-704	-
30.5L-32	20	961	70	371-538	-
35.5L-32	20	1238	81	371-572	-





**FOR SPL CRC SEVERE SVC TLLS2**


Up to 25% better wear and improved cut resistance. A 20% stronger sidewall and 20% stronger base gauge for better puncture resistance.


28L-26	16	733	70	362-511	-
30.5L-32	26	988	70	371-555	-
35.5L-32	24	1296	81	371-606	-


## Current Tire List

Size	Ply	Weight	Tread	Article	Old Article
 <h3><b><u>FORESTRY ENV LUG TL</u></b></h3> <p>Trademarked 23° tread designed as an "environmental lug". For small logging forwarders and harvesters.</p>					
600/55-26.5	20	385	32	<b>359-289</b>	-
700/50-26.5	20	419	32	<b>359-297</b>	-
710/45-26.5	20	436	32	<b>371-623</b>	-















 <h3><b><u>FORESTRY TRACTION LUG TLHF1</u></b></h3> <p>Steel tread plies and special tread and sidewall rubber reduces downtime. Trademarked 23° tread designed as a "traction lug".</p>					
60065B34	14	590	67	<b>359-068</b>	-
70055B34	14	656	67	<b>359-076</b>	-

 <h3><b><u>FLOTATION 23° DT LOGGER WTP TLHF3</u></b></h3> <p>23° deep tread provides a combination of flotation and traction. Delivers up to 20% in fuel savings.</p>					
54X37.00-25	12	726	61	<b>352-063</b>	-
54X37.00-25	20	766	61	<b>373-102</b>	-
66X43.00-25	14	1099	74	<b>354-392</b>	-
66X43.00-26	14	1078	74	<b>354-422</b>	-
68X50.00-32	16	1414	80	<b>343-137</b>	-
73X44.00-32	16	1425	77	<b>343-366</b>	-
76X50.00B32	16	1721	80	<b>359-130</b>	-

 <h3><b><u>FLOTATION 23° DT LOGGER WTP TLHF4</u></b></h3> <p>For logging service on forwarders and harvesters. Extra deep tread for maximum traction in wet swampy areas.</p>					
67X34.00-25	14	1084	112	<b>354-902</b>	-
67X34.00-26	14	1085	112	<b>354-899</b>	-

 <h3><b><u>FLOTATION 23° XDT LOGGER TLHF4</u></b></h3> <p>For logging service on forwarders and harvesters. 23° "environmental lug" tread for excellent traction - even with heavy loads.</p>					
66X43.00-25	14	1366	109	<b>354-325</b>	-
66X43.00-26	14	1350	109	<b>354-333</b>	-

## Current Tire List

Size	Ply	Weight	Tread	Article	Old Article
 <h3><u>RADIAL DURAFORCE AT-R TLR4</u></h3> <p>A new radial R-4 non-directional knobby design that provides superior forward and reverse traction, minimal noise, minimal vibration and improved ride comfort. More resistance to irregular wear patterns.</p>   					
320/80R18 (12.5/80R18)	134A8	96	31	365-656	-
340/80R18 (13.6R18)	136A8	106	32	364-483	-
500/70R24 (19.5LR24)	146A8	241	34	364-534	-
 <h3><u>RADIAL DURAFORCE RT TLR4</u></h3> <p>A new radial R-4 directional design that provides superior traction, minimal noise, minimal vibration and improved ride comfort. More resistance to irregular wear patterns.</p>   					
500/70R24 (19.5LR24)	157A8	250	34	371-657	-
 <h3><u>RADIAL ALL TRACTION UTILITY TLR4</u></h3> <p>Excellent backhoe and construction equipment choice. Gives long tread life on hard surface roads.</p> 					
17.5LR24	2*	202	32	351-989	-
 <h3><u>ALL TRACTION UTILITY TTR4</u></h3> <p>For backhoe and construction equipment on and off the road. Gives long tread life on hard surface roads.</p> 					
14.9-28	8	149	33	306-371	-
 <h3><u>ALL TRACTION UTILITY TLR4</u></h3> <p>For backhoe and construction equipment on and off the road. Gives long tread life on hard surface roads.</p> 					
14.9-24	8	136	33	351-849	-
14.9-24	12	151	33	358-584	-
16.9-24	8	156	34	309-281	-
16.9-24	12	175	34	363-990	-
17.5L-24	8	160	32	315-486	-
17.5L-24	10	176	32	325-880	-
18.4-24	8	178	35	316-083	-
18.4-24	12	201	35	355-224	-
19.5L-24	10	217	34	326-054	-
19.5L-24	12	217	34	322-148	-
21L-24	12	253	35	321-370	-
21L-24	16	276	35	327-727	-
420/70-24	6	137	34	351-040	-
21L-24	18	287	35	372-762	-
16.9-28	8	178	34	354-813	-

Size	Ply	Weight	Tread	Article	Old Article
------	-----	--------	-------	---------	-------------



**ALL TRACTION UTILITY TLR4**

For backhoe and construction equipment on and off the road. Gives long tread life on hard surface roads.



16.9-28	12	191	34	364-007	-
18.4-28	12	218	35	355-410	-
21L-28	14	302	36	356-093	-



**INDUSTRIAL TURF & FIELD TLR3**

Designed for drive axles on golf course, park and cemetery equipment - minimizes turf damage. Gives long tread life on hard surface roads.



19.5L-24	10	223	27	356-190	-
----------	----	-----	----	---------	---



**INDUSTRIAL SPECIAL TLF3**

Designed for front wheels on backhoe loaders. Provides durability and wear on hard soil, asphalt and concrete.



11L-15	8	38	14	316-024	-
11L-15	10	47	14	326-011	-
7.50/8.00-16	10	45	13	314-013	-
11L-16	10	46	14	314-625	-
11L-16	12	46	14	326-089	-
14.5/75-16.1	10	84	19	321-567	-



**TRANSPORT DUPLEX TL NY**

Used on hay balers and other equipment to provide proper load carrying capacity and smooth ride.

15-19.5NHS	14	139	19	370-637	-
------------	----	-----	----	---------	---



**INDUSTRIAL POWER IMPLEMENT TLI3**

Light industrial use. Deep overlapping bar cleats and low profile provide excellent traction and flotation with skid-steer loaders.



12.5L-15	8	42	22	340-561	-
16.5L-16.1	6	81	25	340-618	-
16.5L-16.1	10	103	25	342-467	-

Size	Ply	Weight	Tread	Article	Old Article
------	-----	--------	-------	---------	-------------



**ALL TRACTION UTILITY TTI3**

Excellent tread wear on roads. Special durable rubber compounds.



12.0/12.5-18	12	81	32	342-505C	-
10.0/10.5-20	10	69	24	342-548	-



**ALL TRACTION UTILITY TLI3**

Excellent tread wear on roads. Special durable rubber compounds.



10.5/80-18	10	66	28	351-741	-
12.5-20	10	92	30	358-398C	-



**IND FLOTATION 23° TLG1**

Traction tire for compact tractors. 23° high-flotation tread for excellent traction in all soil conditions.



31X15.50-15	8	68	23	314-420	-
-------------	---	----	----	---------	---



**SUPER TRACTION LOADER TLI3**

Light industrial use. Deep overlapping bar cleats and low profile provide excellent traction and flotation with skid-steer loaders.



27X8.50-15	6	27	13	350-672	-
12.5/80-18	12	93	32	359-912	-



**SUPER TRACTION DUPLEX TL NY**

Light industrial use. Deep overlapping bar cleats provide excellent traction and flotation.



215/65D14NHS 106A2	29	17	365-588	-
14-17.5NHS	10	86	416-177	-
15-19.5NHS	12	117	416-517	-
15-22.5NHS	16	180	359-599	-



**DURAFORCE HEAVY DUTY TL**

Extra-wide lugs for extended life. Rim deflector, heavier ply ratings and tough tread reduces downtime.



265/70D16.5 (10-16.5)	8	50	20	362-123	367-356
305/70D16.5 (12-16.5)	10	62	22	362-131	367-390

Size	Ply	Weight	Tread	Article	Old Article
------	-----	--------	-------	---------	-------------



**DURAFORCE TL**

Extra-wide lugs for extended life. Rim deflector, heavier ply ratings and tough tread reduces downtime.



355/70D16.5	10	88	24	362-158N	371-453
-------------	----	----	----	----------	---------



**DURAFORCE DEEP TREAD TL**

The deep tread DuraForce DT tire. Heavy-duty sidewall, rim deflector and tough rubber compounds keep skid and aerial equipment rolling.



215/70D15 (27x 8.50-15)	8	41	22	360-449	-
260/65D15 (27x10.50-15)	8	46	24	360-457	-
390/60D15 (31x15.50-15)	8	95	30	360-465	-
265/70D16.5 (10-16.5)	8	62	26	360-473	-
305/70D16.5 (12-16.5)	10	86	28	360-414	-
305/70D16.5 (12-16.5)	12	90	28	373-170	-
330/55D16.5	10	81	26	360-481	-
395/55D16.5	12	104	28	360-503	-



**DURAFORCE SUPER DEEP TREAD TL**

Super deep tread for added wear and puncture resistance. Large center tread element for more even wear.



305/70D16.5 (12-16.5)	12	110	47	365-724	-
-----------------------	----	-----	----	---------	---



**DURAFORCE NON-DIRECTIONAL TLNHS**

Designed for skid-loader, aerial and backhoe equipment. Heavy-duty sidewall, tread rubber and aggressive rim deflector.



355/70D17.5 (14-17.5)	10	117	24	361-666	-
355/70D17.5 (14-17.5)	14	126	24	361-674	-
385/65D19.5 (15-19.5)	12	158	25	361-682	-
385/65D19.5 (15-19.5)	16	182	25	361-690	-
385/65D22.5 (15-22.5)	16	205	25	361-704	-
445/65D19.5 (18-19.5)	16	225	28	361-712	-
445/65D22.5 (18-22.5)	16	247	28	361-720	-



**RANCHER TTG1**

Designed for use in vineyards. Tread stays cleaner and provides hold on hills.

8.0/75-15	6	29	25	361-941C	-
-----------	---	----	----	----------	---

Size	Ply	Weight	Tread	Article	Old Article
------	-----	--------	-------	---------	-------------



### **FLOTATION SUPER ALL TERRAIN TL**

New compact tractor tire engineered to minimize soil compaction. Delivers flotation for smooth ride and consistent tread profile regardless of tire size.

215/65D14	4	21	10	<b>365-622</b>	-
265/55D16.5	93A8	30	10	<b>365-350</b>	-
320/55D16.5	89A8	45	11	<b>365-384</b>	-
380/70D19.5	4	88	16	<b>365-639</b>	-
460/60D24	135A8	119	17	<b>365-418</b>	-



### **TURF & FIELD TLG2**

Low-profile design provides excellent traction. Extra flotation for minimum ground disturbance.

29X1200-15	6	41	11	<b>359-785</b>	-
31X13.50-15	8	53	11	<b>354-856</b>	-



### **FARM SERVICE RIB TTNV**

3-rib front tire designed for small ag tractors. Designed for positive steering control in loose soil conditions and side slopes.

4.00-9	2	6	12	<b>344-621B</b>	-
4.50-10	4	7	13	<b>344-648B</b>	-
6-12	4	9	11	<b>344-699B</b>	-



### **FARM SERVICE DIA TTNV**

Small diameter turf tire designed for small tractors. Provides maximum flotation and minimum turf damage on lawns, cemeteries, golf courses and sandy soils.






6-14	4	10	10	<b>344-362B</b>	-
7-14	4	13	11	<b>344-370B</b>	-
9.5-16	4	33	19	<b>344-877B</b>	-
11.2-24	4	61	21	<b>344-869B</b>	-



### **FARM SERVICE LUG-15 TTNV**

Great in hard or soft soil conditions. Low bar angle optimizes traction.

9.5-16	6	43	42	<b>344-907B</b>	-
--------	---	----	----	-----------------	---

Size	Ply	Weight	Tread	Article	Old Article
					
<p><b><u>FARM SERVICE LUG-M TTY</u></b>                      Specially designed for front positions of MFWD tractors. Engineered for optimum ride, comfort and wear.</p>					
180/85D12	4	19	35	364-908B	-
5-14	4	12	32	344-443B	-
8-16	6	30	39	344-508B	-
9.5-22	6	47	43	363-752B	352-381
					
<p><b><u>PILLOW DIA TLNY</u></b>                      High flotation for carts and mowers. Small block tread is gentle on turf.</p>					
24X8.50-14	4	17	11	344-591B	-
31X15.50-15	4	42	11	345-016B	-
					
<p><b><u>PILLOW DIA TTY</u></b>                      High flotation for carts and mowers. Small block tread is gentle on turf.</p>					
212/80D15	4	26	11	344-575B	-
355/80D20	4	82	13	344-982B	-
					
<p><b><u>PILLOW DIA 1 TTY</u></b>                      High flotation for carts and mowers. Small block tread is gentle on turf.</p>					
475/65D20	4	113	17	352-624B	-
					
<p><b><u>AG MOWER M40B TLNY</u></b>                      High flotation design prevents turf damage while mowing. Great traction and hold on hills.</p>					
315/75D15	4	47	11	354-848B	-